

InnoTech Atira, full extension drawer runner with Push to open

- ▶ Drawer, height 54 mm (space required 90 mm), load capacity 30 kg



- ▶ For applications, such as under-oven drawer
- ▶ Distinctive look, high quality surfaces
- ▶ Front panel height and side adjustment
- ▶ Quadro drawer runner with long life steel ball bearing principle
- ▶ Push to open - integrated system for opening in response to a light push

Specification

InnoTech Atira drawer from Hettich. Drawer side profiles and drawer runners in 470 mm nominal length (space required 485 mm). With cover caps for the drawer side profiles. Double walled steel drawer side profile, powder coated in:

a) silver aluminium colour

b) pure matt white

c) metal pigmented anthracite

Load capacity 30 kg to EN 15338 Level 3. Integrated opening system. Front panel is quickly fitted and removed without the need for tools. Optional Push to open Synchronisation.

Optional features

- ▶ Push to open Synchronisation



Further information: www.hettich.com

InnoTech Atira, full extension drawer runner with Push to open

- ▶ Drawer, height 70 mm (space required 106 mm), load capacity 30 kg / 50 kg



- ▶ Distinctive look, high quality surfaces
- ▶ Front panel height and side adjustment
- ▶ Quadro drawer runner with long life steel ball bearing principle
- ▶ Push to open - integrated system for opening in response to a light push

Specification

InnoTech Atira drawer from Hettich. With cover caps for the drawer side profiles. Double walled steel drawer side profile, powder coated in:

- a) silver aluminium colour
- b) pure matt white
- c) metal pigmented anthracite

Drawer runners and drawer side profiles in nominal length and load class:

- a) 260 mm (space required 305 mm), 30 kg
- b) 300 mm (space required 315 mm), 30/50 kg

c) 350 mm (space required 365 mm), 30/50 kg

d) 420 mm (space required 435 mm), 30/50 kg

e) 470 mm (space required 485 mm), 30/50 kg

f) 520 mm (space required 535 mm), 30/50 kg

g) 620 mm (space required 635 mm), 50 kg

Load capacity 30/50 kg to EN 15338 Level 3. Integrated opening system. Front panel is quickly fitted and removed without the need for tools. Optional Push to open Synchronisation

Optional features

- ▶ Interior organisation
- ▶ Push to open Synchronisation



Further information: www.hettich.com

InnoTech Atira, full extension drawer runner with Push to open

- ▶ Pot-and-pan drawer with railing, height 144 mm (space required 190 mm), load capacity 30 kg / 50 kg



- ▶ Distinctive look, high quality surfaces
- ▶ Front panel height and side adjustment
- ▶ Quadro drawer runner with long life steel ball bearing principle
- ▶ Push to open - integrated system for opening in response to a light push
- ▶ With optional TopSide (metal / glass / customised) for closing off the drawer side

Specification

InnoTech Atira drawer from Hettich. With cover caps for the drawer side profiles. Double walled steel drawer side profile, powder coated in:

- a) silver aluminium colour
- b) pure matt white
- c) metal pigmented anthracite

Drawer runners and drawer side profiles in nominal length and load class:

- a) 260 mm (space required 305 mm), 30 kg
- b) 300 mm (space required 315 mm), 30/50 kg

- c) 350 mm (space required 365 mm), 30/50 kg
- d) 420 mm (space required 435 mm), 30/50 kg
- e) 470 mm (space required 485 mm), 30/50 kg
- f) 520 mm (space required 535 mm), 30/50 kg
- g) 620 mm (space required 635 mm), 50 kg

Load capacity 30/50 kg to EN 15338 Level 3. Integrated opening system. Front panel is quickly fitted and removed without the need for tools. Optional Push to open Synchronisation

Optional features

- ▶ TopSide (steel / glass / customised)
- ▶ Interior organisation
- ▶ Push to open Synchronisation



Further information: www.hettich.com

InnoTech Atira, full extension drawer runner with Push to open

- ▶ Pot-and-pan drawer with railing, height 176 mm (space required 222 mm), load capacity 30 kg / 50 kg



- ▶ Distinctive look, high quality surfaces
- ▶ Front panel height and side adjustment
- ▶ Quadro drawer runner with long life steel ball bearing principle
- ▶ Push to open - integrated system for opening in response to a light push
- ▶ With optional TopSide (metal / glass / customised) for closing off the drawer side

Specification

InnoTech Atira drawer from Hettich. With cover caps for the drawer side profiles. Double walled steel drawer side profile, powder coated in:

- a) silver aluminium colour
- b) pure matt white
- c) metal pigmented anthracite

Drawer runners and drawer side profiles in nominal length and load class:

- a) 260 mm (space required 305 mm), 30 kg
- b) 300 mm (space required 315 mm), 30/50 kg

c) 350 mm (space required: 365 mm), 30/50 kg

d) 420 mm (space required 435 mm), 30/50 kg

e) 470 mm (space required 485 mm), 30/50 kg

f) 520 mm (space required 535 mm), 30/50 kg

g) 620 mm (space required 635 mm), 50 kg

Load capacity 30/50 kg to EN 15338 Level 3. Integrated opening system. Front panel is quickly fitted and removed without the need for tools. Optional Push to open Synchronisation.

Optional features

- ▶ TopSide (steel / glass / customised)
- ▶ Interior organisation
- ▶ Push to open Synchronisation



Further information: www.hettich.com

InnoTech Atira, full extension drawer runner with Push to open

- ▶ Pot-and-pan drawer with TopSide, height 144 mm (space required 190 mm), load capacity 30 kg / 50 kg



- ▶ Distinctive look, high quality surfaces
- ▶ Front panel height and side adjustment
- ▶ Quadro drawer runner with long life steel ball bearing principle
- ▶ Push to open - integrated system for opening in response to a light push
- ▶ TopSide (metal / glass / customised) between drawer side profile and railing

Specification

InnoTech Atira drawer from Hettich. With cover caps for the drawer side profiles. Double walled steel drawer side profile, powder coated in:

- a) silver aluminium colour
- b) pure matt white
- c) metal pigmented anthracite

Drawer runners and drawer side profiles in nominal length and load class:

- a) 260 mm (space required 305 mm), 30 kg
- b) 300 mm (space required 315 mm), 30/50 kg
- c) 350 mm (space required: 365 mm), 30/50 kg
- d) 420 mm (space required 435 mm), 30/50 kg

- e) 470 mm (space required 485 mm), 30/50 kg
- f) 520 mm (space required 535 mm), 30/50 kg
- g) 620 mm (space required 635 mm), 50 kg

Side element type:

- a) metal in drawer side profile colour, with railing
- b) clear glass, with railing
- c) customised, with railing
- c) customised, with railing

Load capacity 30/50 kg to EN 15338 Level 3. Integrated opening system. Front panel is quickly fitted and removed without the need for tools. Optional Push to open Synchronisation

Optional features

- ▶ Interior organisation
- ▶ Push to open Synchronisation



Further information: www.hettich.com

InnoTech Atira, full extension drawer runner with Push to open

- ▶ Pot-and-pan drawer with TopSide, height 176 mm (space required 222 mm), load capacity 30 kg / 50 kg



- ▶ Distinctive look, high quality surfaces
- ▶ Front panel height and side adjustment
- ▶ Quadro drawer runner with long life steel ball bearing principle
- ▶ Push to open - integrated system for opening in response to a light push
- ▶ TopSide (metal / glass / customised) between drawer side profile and railing

Specification

InnoTech Atira drawer from Hettich. With cover caps for the drawer side profiles. Double walled steel drawer side profile, powder coated in:

- a) silver aluminium colour
- b) pure matt white
- c) metal pigmented anthracite

Drawer runners and drawer side profiles in nominal length and load class:

- a) 260 mm (space required 305 mm), 30 kg
- b) 300 mm (space required 315 mm), 30/50 kg
- c) 350 mm (space required: 365 mm), 30/50 kg
- d) 420 mm (space required 435 mm), 30/50 kg

- e) 470 mm (space required 485 mm), 30/50 kg
- f) 520 mm (space required 535 mm), 30/50 kg
- g) 620 mm (space required 635 mm), 50 kg

Side element type:

- a) metal in drawer side profile colour, with railing
- b) clear glass, with railing
- c) customised, with railing
- c) customised, with railing

Load capacity 30/50 kg to EN 15338 Level 3. Integrated opening system. Front panel is quickly fitted and removed without the need for tools. Optional Push to open Synchronisation.

Optional features

- ▶ Interior organisation
- ▶ Push to open Synchronisation



Further information: www.hettich.com

InnoTech Atira, full extension drawer runner with Push to open

▶ Internal pot-and-pan drawer with railing, height 144 mm (space required 194 mm), load capacity 30 kg / 50 kg



- ▶ Distinctive look, high quality surfaces
- ▶ Front panel height and side adjustment
- ▶ Quadro drawer runner with long life steel ball bearing principle
- ▶ Push to open - integrated system for opening in response to a light push
- ▶ With optional TopSide (metal / glass / customised) for closing off the drawer side

Specification

InnoTech Atira drawer from Hettich. With cover caps for the drawer side profiles. Double walled steel drawer side profile, powder coated in:

- a) silver aluminium colour
- b) pure matt white
- c) metal pigmented anthracite

Drawer runners and drawer side profiles in nominal length and load class:

- a) 260 mm (space required 314 mm), 30 kg
- b) 300 mm (space required 324 mm), 30/50 kg
- c) 350 mm (space required 374 mm), 30/50 kg
- b) 420 mm (space required 444 mm), 30/50 kg

- e) 470 mm (space required 494 mm), 30/50 kg
- f) 520 mm (space required 544 mm), 30/50 kg
- g) 620 mm (space required 644 mm), 50 kg

Internal front panel type:

- a) aluminium in drawer side profile colour
- b) satin finish glass
- c) customised

Load capacity 30/50 kg to EN 15338 Level 3. Integrated opening system. Front panel is quickly fitted and removed without the need for tools. Optional Push to open Synchronisation.

Optional features

- ▶ TopSide (steel / glass / customised)
- ▶ Interior organisation
- ▶ Push to open Synchronisation



Further information: www.hettich.com

InnoTech Atira, full extension drawer runner with Push to open

▶ Internal pot-and-pan drawer with TopSide, height 144 mm (space required 194 mm), load capacity 30 kg / 50 kg



- ▶ Distinctive look, high quality surfaces
- ▶ Front panel height and side adjustment
- ▶ Quadro drawer runner with long life steel ball bearing principle
- ▶ Push to open - integrated system for opening in response to a light push
- ▶ TopSide (metal / glass / customised) between drawer side profile and railing

Specification

InnoTech Atira drawer from Hettich. With cover caps for the drawer side profiles. Double walled steel drawer side profile, powder coated in:

- a) silver aluminium colour
- b) pure matt white
- c) metal pigmented anthracite

Drawer runners and drawer side profiles in nominal length and load class:

- a) 260 mm (space required 314 mm), 30 kg
- b) 300 mm (space required 324 mm), 30/50 kg
- c) 350 mm (space required 374 mm), 30/50 kg
- b) 420 mm (space required 444 mm), 30/50 kg
- e) 470 mm (space required 494 mm), 30/50 kg
- f) 520 mm (space required 544 mm), 30/50 kg

g) 620 mm (space required 644 mm), 50 kg

Side element type:

- a) metal in drawer side profile colour, with railing
- b) clear glass, with railing
- c) customised, with railing

Internal front panel type:

- c) customised, with railing
- a) aluminium in drawer side profile colour
- b) satin finish glass
- c) customised

Load capacity 30/50 kg to EN 15338 Level 3. Integrated opening system. Front panel is quickly fitted and removed without the need for tools. Optional Push to open Synchronisation.

Optional features

- ▶ Interior organisation
- ▶ Push to open Synchronisation



Further information: www.hettich.com

InnoTech Atira, full extension drawer runner with Push to open

- ▶ Internal drawer, height 70 mm (space required 117 mm), load capacity 30 kg / 50 kg



- ▶ Distinctive look, high quality surfaces
- ▶ Front panel height and side adjustment
- ▶ Quadro drawer runner with long life steel ball bearing principle
- ▶ Push to open - integrated system for opening in response to a light push

Specification

InnoTech Atira drawer from Hettich. With cover caps for the drawer side profiles. Double walled steel drawer side profile, powder coated in:

- a) silver aluminium colour
- b) pure matt white
- c) metal pigmented anthracite

Drawer runners and drawer side profiles in nominal length and load class:

- a) 260 mm (space required 314 mm), 30 kg
- b) 300 mm (space required 324 mm), 30/50 kg
- c) 350 mm (space required 374 mm), 30/50 kg
- b) 420 mm (space required 444 mm), 30/50 kg

- e) 470 mm (space required 494 mm), 30/50 kg
- f) 520 mm (space required 544 mm), 30/50 kg
- g) 620 mm (space required 644 mm), 50 kg

Internal front panel type:

- a) aluminium in drawer side profile colour
- b) satin finish glass
- c) customised

Load capacity 30/50 kg to EN 15338 Level 3. Integrated opening system. Front panel is quickly fitted and removed without the need for tools. Optional Push to open Synchronisation.

Optional features

- ▶ Interior organisation
- ▶ Push to open Synchronisation



Further information: www.hettich.com