

# InnoTech Atira, full extension drawer runner with Push to open Silent

▶ Drawer, height 70 mm (space required 108 mm), load capacity 10 kg / 30 kg / 50 kg



- ▶ Distinctive look, high quality surfaces
- ▶ Front panel height and side adjustment
- ▶ Quadro drawer runner with long life steel ball bearing principle
- ▶ Push to open Silent - opening in response to a light push, silent and soft closing

## Specification

InnoTech Atira drawer from Hettich. With cover caps for the drawer side profiles. Double walled steel drawer side profile, powder coated in:

- a) silver aluminium colour
- b) pure matt white
- c) metal pigmented anthracite

Drawer runners and drawer side profiles in nominal length and load class:

- a) 260 mm (space required 279 mm), 10/30 kg
- b) 300 mm (space required 315 mm), 10/30/50 kg

c) 350 mm (space required 365 mm), 10/30/50 kg

d) 420 mm (space required 435 mm), 30/50 kg

e) 470 mm (space required 485 mm), 30/50 kg

f) 520 mm (space required 535 mm), 30/50 kg

g) 620 mm (space required 635 mm), 50 kg

Load capacity 10/30/50 kg to EN 15338 Level 3. Integrated opening system and soft closing. Front panel is quickly fitted and removed without the need for tools. Optional Push to open Synchronisation.

## Optional features

- ▶ Interior organisation
- ▶ Push to open Synchronisation



Further information: [www.hettich.com](http://www.hettich.com)

# InnoTech Atira, full extension drawer runner with Push to open Silent

▶ Pot-and-pan drawer with railing, height 144 mm (space required 192 mm), load capacity 10 kg / 30 kg / 50 kg



- ▶ Distinctive look, high quality surfaces
- ▶ Front panel height and side adjustment
- ▶ Quadro drawer runner with long life steel ball bearing principle
- ▶ Push to open Silent - opening in response to a light push, silent and soft closing
- ▶ With optional TopSide (metal / glass / customised) for closing off the drawer side

## Specification

InnoTech Atira drawer from Hettich. With cover caps for the drawer side profiles. Double walled steel drawer side profile, powder coated in:

- a) silver aluminium colour
- b) pure matt white
- c) metal pigmented anthracite

Drawer runners and drawer side profiles in nominal length and load class:

- a) 260 mm (space required 279 mm), 10/30 kg
- b) 300 mm (space required 315 mm), 10/30/50 kg

c) 350 mm (space required 365 mm), 10/30/50 kg

d) 420 mm (space required 435 mm), 30/50 kg

e) 470 mm (space required 485 mm), 30/50 kg

f) 520 mm (space required 535 mm), 30/50 kg

g) 620 mm (space required 635 mm), 50 kg

Load capacity 10/30/50 kg to EN 15338 Level 3. Integrated opening system and soft closing. Front panel is quickly fitted and removed without the need for tools. Optional Push to open Synchronisation.

## Optional features

- ▶ TopSide (steel / glass / customised)
- ▶ Interior organisation
- ▶ Push to open Synchronisation



Further information: [www.hettich.com](http://www.hettich.com)

# InnoTech Atira, full extension drawer runner with Push to open Silent

- ▶ Pot-and-pan drawer with railing, height 176 mm (space required 224 mm), load capacity 10 kg / 30 kg / 50 kg



- ▶ Distinctive look, high quality surfaces
- ▶ Front panel height and side adjustment
- ▶ Quadro drawer runner with long life steel ball bearing principle
- ▶ Push to open Silent - opening in response to a light push, silent and soft closing
- ▶ With optional TopSide (metal / glass / customised) for closing off the drawer side

## Specification

InnoTech Atira drawer from Hettich. With cover caps for the drawer side profiles. Double walled steel drawer side profile, powder coated in:

- a) silver aluminium colour
- b) pure matt white
- c) metal pigmented anthracite

Drawer runners and drawer side profiles in nominal length and load class:

- a) 260 mm (space required 279 mm), 10/30 kg
- b) 300 mm (space required 315 mm), 10/30/50 kg

c) 350 mm (space required 365 mm), 10/30/50 kg

d) 420 mm (space required 435 mm), 30/50 kg

e) 470 mm (space required 485 mm), 30/50 kg


f) 520 mm (space required 535 mm), 30/50 kg

g) 620 mm (space required 635 mm), 50 kg

Load capacity 10/30/50 kg to EN 15338 Level 3. Integrated opening system and soft closing. Front panel is quickly fitted and removed without the need for tools. Optional Push to open Synchronisation.

## Optional features

- ▶ TopSide (steel / glass / customised)
- ▶ Interior organisation
- ▶ Push to open Synchronisation



Further information: [www.hettich.com](http://www.hettich.com)

# InnoTech Atira, full extension drawer runner with Push to open Silent

- ▶ Pot-and-pan drawer with TopSide, height 144 mm (space required 192 mm), load capacity 30 kg / 50 kg



- ▶ Distinctive look, high quality surfaces
- ▶ Front panel height and side adjustment
- ▶ Quadro drawer runner with long life steel ball bearing principle
- ▶ Push to open Silent - opening in response to a light push, silent and soft closing
- ▶ TopSide (metal / glass / customised) between drawer side profile and railing

## Specification

InnoTech Atira drawer from Hettich. With cover caps for the drawer side profiles. Double walled steel drawer side profile, powder coated in:

- a) silver aluminium colour
- b) pure matt white
- c) metal pigmented anthracite

Drawer runners and drawer side profiles in nominal length and load class:

- a) 260 mm (space required 279 mm), 10/30 kg
- b) 300 mm (space required 315 mm), 10/30/50 kg
- c) 350 mm (space required 365 mm), 10/30/50 kg
- d) 420 mm (space required 435 mm), 30/50 kg

- e) 470 mm (space required 485 mm), 30/50 kg
- f) 520 mm (space required 535 mm), 30/50 kg
- g) 620 mm (space required 635 mm), 50 kg

Side element type:

- a) metal in drawer side profile colour, with railing
- b) clear glass, with railing
- c) customised, with railing
- c) customised, with railing

Load capacity 10/30/50 kg to EN 15338 Level 3. Integrated opening system and soft closing. Front panel is quickly fitted and removed without the need for tools. Optional Push to open Synchronisation.

## Optional features

- ▶ Interior organisation
- ▶ Push to open Synchronisation



Further information: [www.hettich.com](http://www.hettich.com)

## InnoTech Atira, full extension drawer runner with Push to open Silent

▶ Internal pot-and-pan drawer with railing, height 144 mm (space required: 196 mm), load capacity 10 kg / 30 kg / 50 kg



- ▶ Distinctive look, high quality surfaces
- ▶ Front panel height and side adjustment
- ▶ Quadro drawer runner with long life steel ball bearing principle
- ▶ Push to open Silent - opening in response to a light push, silent and soft closing
- ▶ With optional TopSide (metal / glass / customised) for closing off the drawer side

### Specification

InnoTech Atira drawer from Hettich. With cover caps for the drawer side profiles. Double walled steel drawer side profile, powder coated in:

- a) silver aluminium colour
- b) pure matt white
- c) metal pigmented anthracite

Drawer runners and drawer side profiles in nominal length and load class:

- a) 260 mm (space required 288 mm), 10/30 kg
- b) 300 mm (space required 324 mm), 10/30/50 kg
- c) 350 mm (space required 374 mm), 10/30/50 kg
- b) 420 mm (space required 444 mm), 30/50 kg

- e) 470 mm (space required 494 mm), 30/50 kg
- f) 520 mm (space required 544 mm), 30/50 kg
- g) 620 mm (space required 644 mm), 50 kg

Internal front panel type:

- a) aluminium in drawer side profile colour
- b) satin finish glass
- c) customised

Load capacity 10/30/50 kg to EN 15338 Level 3. Integrated opening system and soft closing. Front panel is quickly fitted and removed without the need for tools. Optional Push to open Synchronisation.

### Optional features

- ▶ TopSide (steel / glass / customised)
- ▶ Interior organisation
- ▶ Push to open Synchronisation



Further information: [www.hettich.com](http://www.hettich.com)

# InnoTech Atira, full extension drawer runner with Push to open Silent

► Internal pot-and-pan drawer with TopSide, height 144 mm (space required: 196 mm), load capacity 10 kg / 30 kg / 50 kg



- Distinctive look, high quality surfaces
- Front panel height and side adjustment
- Quadro drawer runner with long life steel ball bearing principle
- Push to open Silent - opening in response to a light push, silent and soft closing
- TopSide (metal / glass / customised) between drawer side profile and railing

## Specification

InnoTech Atira drawer from Hettich. With cover caps for the drawer side profiles. Double walled steel drawer side profile, powder coated in:

- a) silver aluminium colour
- b) pure matt white
- c) metal pigmented anthracite

Drawer runners and drawer side profiles in nominal length and load class:

- a) 260 mm (space required 288 mm), 10/30 kg
- b) 300 mm (space required 324 mm), 10/30/50 kg
- c) 350 mm (space required 374 mm), 10/30/50 kg
- b) 420 mm (space required 444 mm), 30/50 kg
- e) 470 mm (space required 494 mm), 30/50 kg
- f) 520 mm (space required 544 mm), 30/50 kg

g) 620 mm (space required 644 mm), 50 kg

Side element type:

- a) metal in drawer side profile colour, with railing
- b) clear glass, with railing
- c) customised, with railing

Internal front panel type:

- c) customised, with railing
- a) aluminium in drawer side profile colour
- b) satin finish glass
- c) customised

Load capacity 10/30/50 kg to EN 15338 Level 3. Integrated opening system and soft closing. Front panel is quickly fitted and removed without the need for tools. Optional Push to open Synchronisation.

## Optional features

- Interior organisation
- Push to open Synchronisation



Further information: [www.hettich.com](http://www.hettich.com)

# InnoTech Atira, full extension drawer runner with Push to open Silent

- ▶ Internal drawer, height 70 mm (space required: 120 mm), load capacity 10 kg / 30 kg / 50 kg



- ▶ Distinctive look, high quality surfaces
- ▶ Front panel height and side adjustment
- ▶ Quadro drawer runner with long life steel ball bearing principle
- ▶ Push to open Silent - opening in response to a light push, silent and soft closing

## Specification

InnoTech Atira drawer from Hettich. With cover caps for the drawer side profiles. Double walled steel drawer side profile, powder coated in:

- a) silver aluminium colour
- b) pure matt white
- c) metal pigmented anthracite

Drawer runners and drawer side profiles in nominal length and load class:

- a) 260 mm (space required 288 mm), 10/30 kg
- b) 300 mm (space required 324 mm), 10/30/50 kg
- c) 350 mm (space required 374 mm), 10/30/50 kg
- b) 420 mm (space required 444 mm), 30/50 kg

e) 470 mm (space required 494 mm), 30/50 kg

f) 520 mm (space required 544 mm), 30/50 kg

g) 620 mm (space required 644 mm), 50 kg

Internal front panel type:

- a) aluminium in drawer side profile colour
- b) satin finish glass
- c) customised

Load capacity 10/30/50 kg to EN 15338 Level 3. Integrated opening system and soft closing. Front panel is quickly fitted and removed without the need for tools. Optional Push to open Synchronisation.

## Optional features

- ▶ Interior organisation
- ▶ Push to open Synchronisation



Further information: [www.hettich.com](http://www.hettich.com)