

Intermat 110° standard hinge without self closing feature

▶ Fast assembly hinge without Silent System



- ▶ Attractive, timeless design from elegant, clean cut lines
- ▶ Concealed clip on installation for easy, tool-less hinge installation
- ▶ Convenient, direct adjustment in three dimensions
- ▶ Optional Silent System for gently closing doors

Specification

Intermat fast assembly hinge from Hettich. 9973. Opening angle 110° Without self closing feature for Push to Open applications. For door thicknesses from 15 mm to 25 mm.

Door mounting options for:

- Overlay door
- Half overlay
- Inset door

Types:

- different drilling patterns

- different fastening methods

Mounting plates available:

- cross mounting plate
- linear mounting plate

Quality classification under EN 15570, Level 3. Made in Germany. Fast tool-less installation and removal. Integrated overlay adjustment + 2 mm / - 2 mm. Integrated depth adjustment + 2.5 mm / - 1.5 mm. Height adjustment at mounting plate.

Optional features

- ▶ Cover caps for the side arm
- ▶ Opening angle limiter
- ▶ Optional Silent System
- ▶ Push to open assisted opening



Further information: www.hettich.com

Intermat 95° thick door hinge without self closing feature

- ▶ Fast assembly hinge without Silent System for doors up to 32mm thick



- ▶ Attractive, timeless design from elegant, clean cut lines
- ▶ Concealed clip on installation for easy, tool-less hinge installation
- ▶ Convenient, direct adjustment in three dimensions
- ▶ Optional Silent System for gently closing doors

Specification

Intermat fast assembly hinge from Hettich. 9966. 95° opening angle. Without self closing feature for Push to Open applications. For door thicknesses from 14 mm to 32 mm.

Door mounting options for:

- Overlay door
- Half overlay
- Inset door

Types:

- different drilling patterns

- different fastening methods

Mounting plates available:

- cross mounting plate
- linear mounting plate

Quality classification under EN 15570, Level 2. Made in Germany. Fast tool-less installation and removal. Integrated overlay adjustment + 2 mm / - 2 mm. Integrated depth adjustment + 2.5 mm / - 1.5 mm. Height adjustment at mounting plate.

Optional features

- ▶ Cover caps for the side arm
- ▶ Opening angle limiter
- ▶ Optional Silent System
- ▶ Push to open assisted opening



Further information: www.hettich.com

Intermat 95° angle hinge W90 without self closing feature

- ▶ Fast assembly hinge without Silent System for 90° face angle application



- ▶ Attractive, timeless design from elegant, clean cut lines
- ▶ Concealed clip on installation for easy, tool-less hinge installation
- ▶ Convenient, direct adjustment in three dimensions
- ▶ Optional Silent System for gently closing doors

Specification

Intermat fast assembly hinge from Hettich. 9966 for 90° face angle applications. Opening angle 95° Without self closing feature for Push to Open applications. For door thicknesses from 14 mm to 28 mm.

Door mounting options for:

- Overlay door
- Inset door

Types:

- different drilling patterns

- different fastening methods

Mounting plates available:

- cross mounting plate
- linear mounting plate

Quality classification under EN 15570, Level 2. Made in Germany. Fast tool-less installation and removal. Integrated overlay adjustment + 2 mm / - 2 mm. Integrated depth adjustment + 2 mm / - 2 mm. Height adjustment at mounting plate.

Optional features

- ▶ Cover caps for the side arm
- ▶ Opening angle limiter
- ▶ Optional Silent System
- ▶ Push to open assisted opening



Further information: www.hettich.com